

# CMC-24

## ► Molded Grade IEEE-488 GPIB Cable

### Features

- Economy Cabling Solution
- Normal and Inline Connector
- Double Shielded with Molded Backshells
- Available 0.5m...10m length

### Description

Similar in construction and electrical specifications to our popular CMB24 series with the exception that one end terminates to a straight male connector. This is sometimes preferred when there is no apparent need to have the exposed female end. Furthermore, it eliminates the need for capping the exposed connector. Quite useful when the traditional right angle cable gets in the way of other cables such as in a computer backplane.

The shielding offered by these cables is adequate for many applications. Featuring all-molded connector ends which contribute to long life expectancy, and are impervious to breakage at the point where the cable enters the connector housing. Considerable savings can be realized using this cable, particularly in volume applications.



### Specifications

#### Makeup

**Cable:** 4 Inner Twisted Pairs, 8 Outer Twisted Pairs, Mylar Shield, Drain Wire, Braid Shield, PVC Outer Cover

**Connector:** Cast Metal Nickel Plated Connector, Fully Molded

**Conformance:** STD IEEE-488

## Ordering Information \_\_\_\_\_

CMC24-0M5 - CMC24 0.5 meter length

CMC24-1M - CMC24 1 meter length

CMC24-2M - CMC24 2 meter length

CMC24-3M - CMC24 3 meter length

CMC24-4M - CMC24 4 meter length

CMC24-5M - CMC24 5 meter length

CMC24-10M - CMC24 10 meter length

## On the Web \_\_\_\_\_

Click [www.inesinc.com](http://www.inesinc.com) for more information and resources.



ines Test and Measurement GmbH & Co. KG  
31542 Bad Nenndorf · DE (Germany)  
Phone +49 5723 916 250  
Fax +49 5723 916 252  
Web [www.inesinc.com](http://www.inesinc.com)

All specifications are subject to change without notice. Copyright © 2005. All rights reserved.